



5' AND 6' WIDE PRO SERIES WEDGE CARGO

HEIGHT

- 5' Interior Height (5' Wide Models)
- 6' Interior Height (6' Wide Models)

WEDGE DEPTH

- 13.5" Ext. Wedge Depth

FRAME

- 4" x 2" Tube Frame and Tongue (SA Models)
- 5" x 2" Tube Frame and Tongue (TA Models)
- 16" On-Center Tube Wall Studs
- 24" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Roof Bows

HITCH

- 4-Way Flat Molded Plug (SA Models)
- 7-Way RV-Style Molded Plug (TA Models)
- 2" A-Frame Coupler (SA Models)
- 2-5/16" A-Frame Coupler (TA Models)
- Setback Zinc Plated Jack
- Safety Chains

AXLE

- 4" Drop Spring Axles (SA Models)
- Torsion Axles (TA Models)
- Easy Lube Hubs

WHEELS / TIRES

- 15" Radial Tires on Silver Steel Wheels (5' Wide Models)
- 15" Radial Tires on Aluminum Wheels (6' Wide Models)

INTERIOR

- 3/8" Plywood Wall Liner with Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4" Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12-VOLT ELECTRICAL

- (1) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (1) Wall Switch
- All LED Exterior Lights
- Integrated Backup Lights (TA Models)

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- 24" Stoneguard with Top Trim
- Seamless Aluminum Roof with 3" Top Trim
- Bright Nose Cap & Front Corners
- Bright Rear Hoop
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

DOORS

- 32" x 64" RV Side Door (6' Wide Models)
- Heavy-Duty Rear Ramp Door with Wood Flap
 - **OR** Single Rear Door with Cam Bar and Aluminum Door Holder
- Ramp Rating – 2250 lb.





5' AND 6' WIDE PRO SERIES WEDGE CARGO

	SA 5' x 8'	SA 5' x 10'	SA 6' x 10'	SA 6' x 12'	TA 6' x 12'
Model #	STW6008SA	STW6010SA	STW7210SA	STW7212SA	STW7212TA
GVWR (lb.)	2990	2990	2990	2990	7000
GAWR (lb. / axle)	3500	3500	3500	3500	3500
Curb Weight	950	1100	1240	1390	1880
Payload	2040	1890	1750	1600	5120
Frame	4x2 Tube			5x2 Tube	
Cross Members	C-Channel (24" On-Center)			C-Channel (16" On-Center)	
Tongue	4x2 Tube			5x2 Tube	
Wall Studs				Tube (16" On-Center)	
Roof Bows				Tube (24" On-Center)	
Coupler	2" A-Frame Coupler			2-5/16" A-Frame Coupler	
Jack	Setback 2K Zinc Plated Jack				
Fenders	Aluminum				
Easy Lube Axles	4" Drop Spring Axle			Torsion Axles	
Tires	205/75R 15 LRC				
Wheels	15", 5 on 4.5, Radial				
Wheels	Silver Mod		Aluminum		
Flooring	Engineered Wood				
Lights	All LED Lighting			All LED Lighting w/ Integrated Backup Lights	
Electric Plug	4-Way Flat Molded Plug			7-Way RV-Style Molded Plug	
Exterior	Screwless .030 Aluminum				
Overall Length	150"	174"	174"	198"	198"
Overall Width	80"	80"	92"	92"	92"
Overall Height	80"	80"	93"	93"	93"
Interior Height	59"	59"	72"	72"	72"
Interior Width	57"	57"	69"	69"	69"
Interior Length	108"	132"	132"	156"	156"
Floor Height	18"	18"	18"	18"	18"
Rear Door Opening (WxH)	50" x 53.75"	50" x 53.75"	62" x 66.75"	62" x 66.75"	62" x 66.75"
Ramp Door Capacity (lbs.)	2250	2250	2250	2250	2250

