

G125WCU-3A-T4F

Model	G125		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	151	100	125
@ 240V-3Ø, 0.8PF, 60Hz	301	100	125
@ 208V-3Ø, 0.8PF, 60Hz	336	97	121
@ 240V-1Ø, 1.0PF, 60Hz	360	86.5	86.5
@ 120V-1Ø, 1.0PF, 60Hz	360 × 2	86.5	86.5
@ 400V-3Ø, 0.8PF, 50Hz	152	84	105
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		
ENGINE			
Engine Make / Model	Cummins QSB5-G11		
Displacement (L)	4.5		
Number of Cylinders	4		
Power Output @ 1800RPM - HP (kWm)	153 (114)		
Emissions Tier Level	Tier 4 Final		
Aftertreatment Technology	DOC / SCR		
Usable Fuel Tank Capacity - Gal (L)	176.5 (668)		
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	24.4 (92.4)		
Runtime @ 100% Load - Hr	24.5		
DIMENSIONS WITH RUNNING GEAR			
Length - in (mm)	171 (4343)		
Width - in (mm)	72.5 (1841)		
Height - in (mm)	91.0 (2311)		
Weight (Ready to Run) - lb (kg)	6950 (3152)		
Sound Level @ 23 ft (7m) and 100%	68		

**MAKE POWER MOVES.****DoosanPowerMoves.com | 800.633.5206**

© 2020 Doosan Portable Power. All rights reserved.

Doosan reserves the right to limit quantities, alter lead times or cancel models without prior notice or obligation. Nothing contained in this brochure intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale shall be in accordance with standard Doosan Portable Power terms and conditions of sale for such products, which are available upon request. Specifications in this brochure are subject to change without notice.