



HD LOW PROFILE BEAVERTAIL DECKOVER - BUMPER PULL

	8.5' x 20' + 5' (15K)	8.5' x 20' + 5' (17.6K)	8.5' x 20' + 5' (22.5K)	8.5' x 20' + 5' (26K)	8.5' x 20' + 5' (32K)
Model #	ST102205LPDO2A-B-150	ST102205LPDO2A-B-176	ST102205LPDO2A-B-225	ST102205LPDO2A-B-259	ST102205LPDO2A-B-320
GVWR (lb.)	15000	17600	22500	25900	32000
GAWR (lb. / axle)	7000	8000	10000	12000	16000
Curb Weight	4640	4740	5540	5840	6210
Payload	10360	12860	16960	20060	25790
Main Frame	W12 x 14#/ft., I-Beam				W12 x 19#/ft., I-Beam
Side Rails	5" C-Channel				6" C-Channel
Cross Members	3" C-Channel (16" On-Center)				
Beavertail	Self-Cleaning Cleats				
Coupler	Adjustable Pintle Eye Coupler				Adjustable 4-Bolt Pintle Eye Coupler
Jack	Setback HD 12K Drop Leg Jack				
Axles	E-Z Lube Electric Brake		Oil Bath Bearing		
Suspension	Slipper Spring				
Tires	235/80R16 LRE	215/75R17.5 LRH	235/80R16 LRE	235/80R16 LRE Dual	215/75R 17.5 LRH Dual
Wheels	16", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial	16", 8 on 6.5, Radial	16", 8 on 6.5, Radial	16", 8 on 6.5, Radial
Decking	2" Pressure Treated Pine				
Lights	All LED Lights				
Electric Plug	7-Way RV-Style Molded Plug				
Finish	Powder Coated High Gloss Black				
Overall Length	378"	378"	378"	378"	378"
Deck Height	32"	32"	32"	32"	32"
Coupler Height	Adjustable 21"-29"				
Ramps	HD Fabricated Fold-Flat with Double Hinged Spring-Assist				

HD LOW PROFILE BEAVERTAIL DECKOVER - BUMPER PULL FEATURES

Pierced I-Beam Frame	Setback HD 12K Drop Leg Jack	Wheel Assembly, 215 75R17.5 (17.6K Models)
Cross Trac Bracing, Four Times Stronger than Torque Tube	5' Self-Cleaning Beavertail	Wheel Assembly, 235 80R16 LRE 4.77 Silver Dual (22.5K & 25.9K Models)
HD I-Beam Tongue	Spring-Assist Flip-Over Ramps	Wheel Assembly, 215 75R17.5 LRH Silver Dual (32K Models)
Heavy Duty Steel Bulkhead	HD Slipper Spring Axles	Powder Coat Finish
Adjustable Pintle Eye Coupler (15K Models)	48" Axle Spread (22.5K+ Models)	Pressure Treated 2" x 6" Decking
Adjustable 4-Bolt Pintle Eye Coupler (17.6K+ Models)	Easy Lube Hubs (15K & 17.6K Models)	Diamond Plate Deck Over Wheels
Safety Chains	Oil Filled Hubs (22.5K+ Models)	(10) 5/8" D-rings
7-Way RV-Style Molded Plug	16" Radial Tires (15K & 22.5K Models)	Chain Spools
Breakaway Switch with Battery	17.5" Radial Tires (17.6K & 32K Models)	Stake Pockets and Rub Rail
EverLink™ Wiring Harness	Silver Wheels	Spare Tire Carrier
Sealed Brake Connections	Wheel Assembly, 235 80R16 LRE (15K Models)	Side Steps
		All LED Lights





HD LOW PROFILE BEAVERTAIL DECKOVER - GOOSENECK

	8.5' x 20' + 5' (15K)	8.5' x 20' + 5' (17.6K)	8.5' x 20' + 5' (22.5K)	8.5' x 20' + 5' (26K)	8.5' x 20' + 5' (30K)
Model #	ST102205LPDO2A-GN-150	ST102205LPDO2A-GN-176	ST102205LPDO2A-GN-225	ST102205LPDO2A-GN-259	ST102205LPDO2A-GN-300
GVWR (lb.)	15000	17600	22500	25900	30000
GAWR (lb. / axle)	7000	8000	10000	12000	16000
Curb Weight	4930	5030	5800	6100	6470
Payload	10070	12570	16700	19800	23530
Main Frame	W12 x 14#/ft., I-Beam				W12 x 19#/ft., I-Beam
Side Rails	5" C-Channel		6" C-Channel		
Cross Members	3" C-Channel (16" On-Center)				
Beavertail	Self-Cleaning Cleats				
Coupler	Adjustable 2-5/16" Gooseneck Coupler				
Jack	Dual Setback HD 12K Drop Leg Jacks with Toolbox				
Axles	E-Z Lube Electric Brake		Oil Bath Bearing		
Tires	235/80R16 LRE	215/75R17.5 LRH	235/80R16 LRE	235/80R16 LRE Dual	215/75R17.5 LRH Dual
Wheels	16", 8 on 6.5, Radial Silver Spoke	17.5", 8 on 6.5, Radial Grey	16", 8 on 6.5, Radial Grey	16", 8 on 6.5, Radial Silver Spoke	16", 8 on 6.5, Radial Grey
Decking	2" Pressure Treated Pine				
Lights	All LED Lights				
Electric Plug	7-Way RV-Style Molded Plug				
Finish	Powder Coated High Gloss Black				
Overall Length	426"	426"	426"	426"	426"
Deck Height	32"	32"	32"	32"	32"
Coupler Height	Adjustable 31" - 39.75"				
Ramps	HD Fabricated Fold-Flat with Double Hinged Spring-Assist				

HD LOW PROFILE BEAVERTAIL DECKOVER - GOOSENECK FEATURES

Pierced I-Beam Frame	5' Self-Cleaning Beavertail	Wheel Assembly, 235 80R16 LRE 4.77 Silver Dual (22.5K & 25.9K Models)
Cross Trac Bracing, Four Times Stronger than Torque Tube	Spring-Assist Flip-Over Ramps	Wheel Assembly, 215 75R17.5 LRH Silver Dual (30K Models)
I-Beam Gooseneck	HD Slipper Spring Axles	Powder Coat Finish
Heavy Duty Steel Bulkhead	48" Axle Spread (22.5K+ Models)	Pressure Treated 2" x 6" Decking
Adjustable 2-5/16" Gooseneck Coupler	Easy Lube Hubs (15K & 17.6K Models)	Diamond Plate Deck Over Wheels
Safety Chains	Oil Filled Hubs (22.5K+ Models)	(10) 5/8" D-rings
7-Way RV-Style Molded Plug	16" Radial Tires (15K & 22.5K Models)	Chain Spools
Breakaway Switch with Battery	17.5" Radial Tires (17.6K & 32K Models)	Stake Pockets and Rub Rail
EverLink™ Wiring Harness	Silver Wheels	Spare Tire Carrier
Sealed Brake Connections	Wheel Assembly, 235 80R16 LRE (15K Models)	Side Steps
Dual Setback HD 12K Drop Leg Jacks with Toolbox	Wheel Assembly, 215 75R17.5 (17.6K Models)	All LED Lights

