

ST PRO SERIES ROUND TOP CAR HAULER

HEIGHT

- 6'6" Interior Height

FRAME

- 6" x 2" Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- Triple-Tube Tongue
- 24" On-Center Tube Roof Bows
- 48" Beavertail (24" on 16' unit)

HITCH

- 7-Way RV-Style Molded Plug
- 2-5/16" A-Frame Coupler (7K & 10K Models)
- Adjustable 2-5/16" Coupler (14K Models)
- Setback Zinc Plated Jack (7K Models)
- Setback 7K Drop Leg Jack (10K & 14K Models)
- Safety Chains

AXLES

- Torsion Axles
- All Wheel Brakes
- Easy Lube Hubs

WHEELS / TIRES

- Radial Tires on Aluminum Wheels (up to 14K)

INTERIOR

- 3/8" Plywood Wall Liner with Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4" Engineered Wood Flooring
- (4) 6K D-rings
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12-VOLT ELECTRICAL

- (2) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (1) Wall Switch
- All LED Exterior Lights
- Integrated Backup Lights

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- Bright Front Corners
- Bright Rear Hoop
- 24" Stoneguard with Top Trim
- .080 Aluminum Roof Cove with Seamless Aluminum Roof
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

DOORS

- 48" x 70" RV Side Door with Step Well and Aluminum Door Holder
- Heavy-Duty Rear Ramp Door with Wood Flap
 - Ramp Rating – 4100 lb.





PRO SERIES ROUND TOP CAR HAULER

		7K	10K
Model #	18'	STRCH10218TA	STRCH10218TA-100
	20'	STRCH10220TA	STRCH10220TA-100
	24'	N/A	STRCH10224TA-100
	28'	N/A	STRCH10228TA-100
GVWR (lb.)		7000	9900
GAWR (lb. / axle)		3500	5200
Curb Weight	18'	3250	3450
	20'	3425	3600
	24'	N/A	3900
	28'	N/A	4325
Payload	18'	3750	6450
	20'	3575	6300
	24'	N/A	6000
	28'	N/A	5575
Frame	6x2, 1/8" Tube		
Cross Members	C-Channel (16" On-Center)		
Tongue	6x2, 1/8" Tube		
Wall Studs	Tube (16" On-Center)		
Roof Bows	Tube (24" On-Center)		
Coupler	2-5/16" A-Frame Coupler		
Jack	Setback 2K Zinc Plated jack		Setback 7K Drop Leg Jack
Fenders	Aluminum Teardrop		
Easy Lube Axles	Torsion Axles		
Tires	205/75R 15 LRC		225/75R15 LRD
Wheels	15", 5 on 4.5, Radial		15", 6 on 5.5, Radial
Wheels	Aluminum		
Flooring	Engineered Wood		
Lights	All LED Lights w/ Integrated Backup Lights		
Electric Plug	7-Way RV-Style Molded Plug		
Exterior	Screwless .030 Aluminum		
Overall Length	18'	273"	
	20'	297"	
	24'	345"	
	28'	393"	
Overall Width	102"		
Overall Height	101"		101"
Interior Height	81"		
Interior Width / Between Fenders	97" / 80.5"		
Interior Length	18'	225"	
	20'	249"	
	24'	297"	
	28'	345"	
Floor Height	21"		21"
Rear Door Opening (WxH)	90" x 76.50		
Ramp Door Capacity (lb.)	4100		

**14K GVWR Includes
Adjustable 2-5/16" Coupler and Setback 7K Drop Leg Jack**

