

## DUAL PRESSURE

**375**

cfm  
@ 100 psi

**330**

cfm  
@ 150 psi



Available with optional



### PERFORMANCE //

- 1 - Digital Touch Screen Control
- 2 - Emergency Shut-off Button
- 3 - Quick Access Air Connections
- 4 - Direct Coupled Engine to Air
- 5 - QuieTech™ Sound Attenuation
- 6 - E2 Airflow Technology

### MAINTENANCE //

- 7 - Large Gullwing Doors
- 8 - Curbside Filter Servicing
- 9 - Compressor Oil Access Door
- 10 - After Cooler Access Door
- 11 - Curbside Fuel Drain
- 12 - Exterior Service Drains
- 13 - Front SCR Access Panel

### CONSTRUCTION //

- 14 - Stainless Steel Hardware
- 15 - Powder-coated Steel Enclosure
- 16 - Lockable Access Doors
- 17 - Automotive Door Seals
- 18 - 47 Gallon Fuel Tank
- 19 - Heavy-Duty Steel Tow Trailer



**Kubota®**  
V3800  
Tier 4 / CARB  
Diesel Engine




**1 | Digital Touch Screen Control** with Start Button & Pressure Selector Switch



**3 | Air Connections**  
3/4" Ball Valve x 2 | 2" Ball Valve x 1



**12 | Exterior Service Drains**  
Quick drain valves for the Radiator, Oil Cooler and Engine Oil fluids



**13 | Front-mounted SCR System**  
Convenient access for easy servicing

**BEST-IN-CLASS POWER TRANSFER // FUEL EFFICIENCY // dBA RATING**  
**THE INDUSTRY'S HIGHEST-QUALITY MOBILE AIR COMPRESSORS**



# AIR COMPRESSOR MODEL PDSF375DP/DPC-6E1 (AFTER COOLER)

# RUN WITH AIRMAN®

AIR COMPRESSOR SPECIFICATIONS	
COMPRESSOR TYPE	Single-Stage Oil Cooled, Screw Type
<b>DUAL PRESSURE 375 CFM @ 100 PSI</b>	
375 ACTUAL FREE AIR DELIVERY	375 cfm
WORKING PRESSURE	100 psig
WORKING PRESSURE (MAXIMUM)	120 psig
WORKING PRESSURE (MINIMUM)	58 psig
<b>DUAL PRESSURE 330 CFM @ 150 PSI</b>	
330 ACTUAL FREE AIR DELIVERY	330 cfm
WORKING PRESSURE	150 psig
WORKING PRESSURE (MAXIMUM)	180 psig
WORKING PRESSURE (MINIMUM)	58 psig
COMPRESSOR LUBRICATING OIL CAP.	10.5 gal
COMPRESSOR LUBRICATING SYSTEM	Forced Lubrication by Compressed Air
DRIVING SYSTEM	Direct Drive w/Rubber Damper Coupling
RECEIVER TANK CAPACITY	20.3 g/min
AIR SERVICE VALVES	3/4" Male Ball Valve x 2
SEPERATION FILTERS	2" Female Ball Valve x 1
OIL COOLER TYPE	Internal Oil Separator
COMPRESSOR OIL FILTER	Air Pressurized Tube and Fin
SOUND dBA RATING	Spin-on Cartridge Type
<b>ENGINE MAKE &amp; MODEL</b>	<b>KUBOTA® V3800TIEF4B-COHE-1</b>
ENGINE TYPE	4-cycle, Water-cooled,
ASPIRATION	Direct injection, Diesel
NUMBER OF CYLINDERS	Turbocharged + Turbo After Cooler
	4

ENGINE MAKE & MODEL (Continued)	
ENGINE DISPLACEMENT	230 cu in
HORSEPOWER RATING (@2600 RPM)	104.5 HP / 77.9 kW
SAE BRAKE HORSEPOWER (@2600 RPM)	114.1 HP
OPERATING SPEED (LOW IDLE)	1300 rpm
OPERATING SPEED (HIGH IDLE)	2600 rpm
EPA TIER 4F	CARB Exec. Order U-R-025-0929
CARB EMISSION CERTIFIED 2021	EPA Cert. No. MKBXL03.8AMD-055
EMISSIONS TIER	EPA Tier 4 Final
EMISSIONS TYPE	DOC, PTOX-DPF, ASC, SCR, EGR
FUEL TANK CAPACITY	47.0 gal
FUEL FILTER QUANTITY/TYPE	1 Pre-filter, 1 Sediment, 1 Fuel Filter
FUEL PUMP	Fuel Air-bleeding Electric Pump w/Filter
DIESEL EXHAUST FLUID (DEF) CAPACITY	5.3 gal
DEF CONSUMPTION	0.12 gal/hr
ENGINE OIL CAPACITY	3.4 gal
COOLANT CAPACITY	4.12 gal
ELECTRICAL SYSTEM - VOLTAGE	12V, 90A Alternator
BATTERY RATING	695 CCA / 120 Ah
BATTERY GROUP	130F51, 12V
AMBIENT TEMPERATURE (MIN./MAX.)	5° F to 104° F, Humidity <80%
OPERATING ALTITUDE (MAXIMUM)	4,921 ft
RUNTIME (FULL LOAD / 70% LOAD)	9.1 hrs / 13.8 hrs
CONTAINMENT	No Fluid Containment
<b>FUEL CONSUMPTION</b>	
FULL LOAD	5.12 gal/hr
70% LOAD	3.40 gal/hr
NO LOAD	1.58 gal/hr

WEIGHTS & DIMENSIONS	
LENGTH x WIDTH x HEIGHT	103.5" x 57.3" x 47.6"
DRY WEIGHT/ WITH AFTERCOOLER	3,737 lbs / 3,803 lbs
OPERATING WT./ WITH AFTERCOOLER	4,233 lbs / 4,299 lbs
LENGTH	103.5"
WIDTH	57.3"
HEIGHT	47.6"
<b>TOWING PACKAGE</b>	
LENGTH x WIDTH x HEIGHT	174" x 77.75" x 69"
LENGTH	174"
WIDTH	77.75"
HEIGHT	69"
OPERATING WEIGHT w/TOWING (GVWR)	4,653 lbs / 4,719 w/After Cooler
TOWING SPEED (MAXIMUM)	65 mph - Conditions Permitting
TRACK WIDTH TOW PACKAGE	68"
WHEEL SIZE - TIRE RATING	ST235/80R16E / 3,520 lbs @ 80psi
NUMBER OF AXLES / RATING	1 Spring Axle / 5,300 lbs
BRAKING TYPE	Electric w/Breakaway Battery System
LIGHTING TYPE	LED
ADJUSTABLE HITCH HEIGHT	3-Position
<b>COMPLIANCE &amp; CERTIFICATIONS</b>	
FLUID CONTAINMENT	No Fluid Containment
USA DOT COMPLIANT	Meets FMVSS
CSA LISTED	Not CSA Listed
TRANSPORT CANADA COMPLIANT	Transport Canada Compliant
DIESEL ENGINE EPA TIER LEVEL	Tier 4 Final & CARB Compliant

All specifications are subject to change without prior notice. Visit [anacorp.com](http://anacorp.com) for the most current information.

## OPTIONAL ACCESSORIES



Integrated After Cooler



Double Hose Reel Kit



Single Hose Reel Kit



Battery Charger



Engine Block Heater



Battery Blanket



SOLD AND SERVICED BY

**ANA N. California**  
1315 Vinci Avenue  
Sacramento, CA 95838

**ANA South Carolina**  
1335 Hayne Street  
Spartanburg, SC 29301

**ANA Texas**  
10440 Brockwood Road  
Dallas, TX 75338



**Alliance North America, Inc.**  
Corporate Headquarters  
11100 Hope Street, Cypress, CA 90630

**ANACORP.COM**  
(562) 450-3570 // [sales@anacorp.com](mailto:sales@anacorp.com)



We make your world easier.

© 2021 Alliance North America, Inc. All rights reserved.

Airman® is a registered trademark of Hokuetsu Industries Co. Ltd. All other trademarks are property of their respective owners.  
Form AMAC375REV1021