

ST CONTRACTOR PRO BULLNOSE

HEIGHT

- 6'6" Interior Height

FRAME

- 6" x 2" Tube Frame and Tongue
- 6" x 2" Tube Frame and Tongue
- 6" Extended Tongue
- Tri-Tongue on 8.5' Wides
- 16" On-Center Tube Wall Studs
- 12" On-Center C-Channel Floor
- Crossmembers
- 16" On-Center Tube Roof Bows
- Flat Deck
- X-Braced Walls, ALL wall posts have 4"x4" gussets reinforced to frame and 9"x14" Corner Gussets

HITCH

- 7-Way RV-Style Molded Plug
- Adjustable 2-5/16" Coupler (10K & 14K Models)
- Adjustable 4-Bolt Pintle Eye Coupler (16K Models)
- Setback 7K Drop Leg Jack (10K & 14K Models)
- Setback HD 12K Drop Leg Jack (16K Models)
- Safety Chains

AXLES

- Torsion Axles
- Easy Lube Hubs

WHEELS / TIRES

- Radial Tires on Aluminum Wheels
- Radial Tires on Solid Silver Wheel (16K Models)

INTERIOR

- 3/8" Plywood Wall Liner with Aluminum H-Trim (Eliminates Staped Lauan Trim)
- 3/4" Engineered Wood Flooring
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)
- Flat Front Full-Width Interior Wall

12-VOLT ELECTRICAL

- (2) 12-Volt Wall Mounted LED Dome Light (380 Lumens) with (2) 3-Way Wall Switches
- (3) Amber Front Marker Lights in Fiberglass Cap
- All LED Exterior Lights
- Integrated Backup Lights

EXTERIOR

- .030 Smooth Aluminum Exterior
- Screwless Exterior
- 24" Stoneguard with Top Trim
- Seamless Aluminum Roof with 3" Top Trim
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

DOORS

- 32" x 70" RV Side Door with Barlock Add-On and Aluminum Door Holder
- Heavy Duty Ramp Door with Integrated Transition
 - **OR** Rear Double Doors with Aluminum Rear Door Holders
- Ramp Rating – 8.5' Wide = 4100 lb.



ST CONTRACTOR PRO BULLNOSE

		8.5' (10K)	8.5' Wide (14K)	8.5' Wide (16K)
Model #	16'	STBNCP10216TA-100	STBNCP10216TA-140	STBNCP10216TA-160
	18'	STBNCP10218TA-100	STBNCP10218TA-140	STBNCP10218TA-160
	20'	STBNCP10220TA-100	STBNCP10220TA-140	STBNCP10220TA-160
	24'	STBNCP10224TA-100	STBNCP10224TA-140	STBNCP10224TA-160
GVWR (lb.)	9900	14000	16000	
GAWR (lb. / axle)	5200	7000	8000	
Curb Weight	16'	3450	3600	4100
	18'	3600	3750	4250
	20'	3750	4080	4580
	24'	4050	4780	5280
Payload	16'	6450	10400	11900
	18'	6300	10250	11750
	20'	6150	9920	11420
	24'	5850	9220	10720
Frame	6 x 2, 3/16" Tube	6 x 2, 3/16" Tube	8x2 Tube	
Cross Members	C-Channel (12" On-Center)	Tube (12" On-Center)		
Tongue	6 x 2, 3/16" Tube	6 x 2, 3/16" Tube	8x2 Tube	
Wall Studs		Tube (16" On-Center)		
Roof Bows		Tube (16" On-Center)		
Coupler	Adjustable 2-5/16" Coupler	Adjustable 2-5/16" Coupler	Adjustable 4-Bolt Pintle Eye Coupler	
Jack	Setback 7K Drop Leg Jack		Setback HD 12K Drop Leg Jack	
Fenders	Aluminum Teardrop			
Easy Lube Axles	Torsion Axles			
Tires	225/75R15 LRD	235/80R16 LRE	215/75R17.5 LRH	
Wheels	15", 6 on 5.5, Radial	16", 8 on 6.5, Radial	17.5", 8 on 6.5, Radial	
Wheels	Aluminum			
Flooring	Engineered Wood			
Lights	All LED Lights w/ Integrated Backup Lights			
Electric Plug	7-Way RV-Style Molded Plug			
Exterior	Screwless .030 Aluminum			
Overall Length	16'	252"		
	18'	279"		
	20'	303"		
	24'	351"		
Overall Width	102"			
Overall Height	104"	106"	106"	
Interior Height	78"			
Interior Width	97" / 80.50"			
Interior Length	16'	192"		
	18'	216"		
	20'	240"		
	24'	288"		
Floor Height	21"	23"	23"	
Rear Door Opening (WxH)	92" x 82.50"			
Ramp Door Capacity (lbs.)	4100			

14K GVWR Includes
Adjustable 2-5/16" Coupler and Setback 7K Drop Leg Jack
16K GVWR Includes
Adjustable 4-Bolt Pintle Eye Coupler and Setback HD 12K Drop Leg Jack

