

**G325WCU-3B-T4F**

Model	G325WCU		
<b>PRIME POWER RATING</b>	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	401	267	334
@ 240V-3Ø, 0.8PF, 60Hz	803	267	334
@ 208V-3Ø, 0.8PF, 60Hz	877	253	316
@ 240V-1Ø, 1.0PF, 60Hz	821	197	197
@ 120V-1Ø, 1.0PF, 60Hz	821 × 2	197	197
@ 400V-3Ø, 0.8PF, 50Hz	404	224	280
Voltage Configuration	Link Board Panel		
Frequency Capability	50Hz/60Hz Switchable		
<b>ENGINE</b>			
Engine Make / Model	Cummins QSL9-G9		
Displacement (L)	8.9		
Number of Cylinders	6		
Power Output @ 1800RPM - HP (kWm)	393 (293)		
Emissions Tier Level	Tier 4 Final		
Aftertreatment Technology	DOC / SCR		
Usable Fuel Tank Capacity - Gal (L)	460 (1741)		
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	24.4 (92.4)		
Runtime @ 100% Load - Hr	24.1		
<b>DIMENSIONS WITH RUNNING GEAR</b>			
Length - in (mm)	240 (6098)		
Width - in (mm)	83 (2109)		
Height - in (mm)	113 (2870)		
Weight (Ready to Run) - lb (kg)	14032 (6378)		
Sound Level @ 23 ft (7m) and 100%	76		

**MAKE POWER MOVES.****DoosanPowerMoves.com | 800.633.5206**

© 2020 Doosan Portable Power. All rights reserved.

Doosan reserves the right to limit quantities, alter lead times or cancel models without prior notice or obligation. Nothing contained in this brochure intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale shall be in accordance with standard Doosan Portable Power terms and conditions of sale for such products, which are available upon request. Specifications in this brochure are subject to change without notice.