

G50WDO-3A-T4F

Model	G50		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	58	38	48
@ 240V-3Ø, 0.8PF, 60Hz	115	38	48
@ 208V-3Ø, 0.8PF, 60Hz	125	36	45
@ 240V-1Ø, 1.0PF, 60Hz	140	33.6	33.6
@ 120V-1Ø, 1.0PF, 60Hz	140 × 2	33.6	33.6
@ 400V-3Ø, 0.8PF, 50Hz	58	32	40
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		
ENGINE			
Engine Make / Model	Doosan D24		
Displacement (L)	2.392		
Number of Cylinders	4		
Power Output @ 1800RPM - HP (kWm)	59.8 (44.6)		
Emissions Tier Level	Tier 4 Final		
Aftertreatment Technology	DOC		
Usable Fuel Tank Capacity - Gal (L)	110 (416)		
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	N/A		
Runtime @ 100% Load - Hr	37.2		
DIMENSIONS WITH RUNNING GEAR			
Length - in (mm)	130.5 (3315)		
Width - in (mm)	72.8 (1850)		
Height - in (mm)	78.4 (1992)		
Weight (Ready to Run) - lb (kg)	3870 (1755)		
Sound Level @ 23 ft (7m) and 100%	64		

**MAKE POWER MOVES.****DoosanPowerMoves.com | 800.633.5206**

© 2020 Doosan Portable Power. All rights reserved.

Doosan reserves the right to limit quantities, alter lead times or cancel models without prior notice or obligation. Nothing contained in this brochure intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale shall be in accordance with standard Doosan Portable Power terms and conditions of sale for such products, which are available upon request. Specifications in this brochure are subject to change without notice.