

PRO-WALK[®] HYDRO

PUT A LITTLE SWAGGER IN YOUR STEP.

Redesigned steering makes the Pro-Walk[®] Hydro easier to operate in any situation. The Pro-Walk commercial walk behind has been updated with the user in mind. A more ergonomic design combines with the stability you trust for precise, comfortable control.

4YR
FOUR YEAR OR 750 HOUR
WARRANTY
NO HOUR LIMIT FOR THE FIRST TWO YEARS



FLIP-UP SIDE DISCHARGE CHUTE reduces damage to the surrounding environment.

WIDE WHEEL BASE for superior hillside stability.

SINGLE-POINT HEIGHT-OF-CUT provides optimal cutting performance in 1/4-inch increments.

INTUITIVE STEERING CONTROLS offer a shortened learning curve while providing precision handling.

CONSTANT BELT TENSION SYSTEM (CBT) ensures the belt tension is constant, blade tip speed is consistent and cutting results are right on the money.

ERGONOMIC CONTROLS user-centered design puts controls where your hands fall naturally to minimize fatigue.



GRAVELY[®]

36HR					48HE					52HE					60HE				
MODEL NUMBER		988184			988185			988186			988187								
ENGINE		KAWASAKI® FS481V			KAWASAKI® FS600V			KAWASAKI® FS600V			KAWASAKI® FS691V								
HORSEPOWER		14.5 HP			18.5 HP			18.5 HP			23 HP								
DISPLACEMENT		603 CC			603 CC			603 CC			726 CC								
DRIVE SYSTEM					HYDRO-GEAR® ZT-2800 TRANSAXLE														
FUEL CAPACITY					5.8 GAL.														
GROUND SPEED (Approx. Mph) (Forward/Reverse)		8 MPH / 3 MPH			8 MPH / 3 MPH			8 MPH / 3 MPH			8 MPH / 3 MPH								
STARTER					ELECTRIC														
DECK																			
DECK MATERIAL		10 GA.			10 GA.			10 GA.			10 GA.								
DECK CONSTRUCTION					WELDED														
NUMBER OF SPINDLES		2			3			3			3								
BLADE TIP SPEED (FPM)					18,000														
SPINDLE HOUSING MATERIAL					FORGED ALUMINUM														
SPINDLE BEARINGS					BALL BEARING														
DECK ENGAGEMENT					ELECTRIC CLUTCH														
DECK LIFT SYSTEM					MANUAL														
CUTTING WIDTH		36 IN.			48 IN.			52 IN.			60 IN.								
CUTTING HEIGHTS		1.5 IN. - 4.5 IN.			1.5 IN. - 5.0 IN.			1.5 IN. - 5.0 IN.			1.5 IN. - 5.0 IN.								
CUTTING POSITIONS (1/4 IN. Increments)		13			15			15			15								
WHEELS																			
FRONT AXLE					RIGID														
FRONT WHEELS					11 X 4-5 SEMI-PNEUMATIC														
REAR		21 X 7-10			20 X 8-10			20 X 8-10			20 X 8-10								
MACHINE																			
WEIGHT		701 LBS.			740 LBS.			770 LBS.			795 LBS.								
LENGTH		80.5 IN.			75.5 IN.			77.5 IN.			78.3 IN.								
WIDTH		36.8 IN.			50.1 IN.			55.5 IN.			63 IN.								
HEIGHT					45 IN.														
WARRANTY																			
UNIT					4 YEAR / 750 HOUR / NO HOUR LIMIT FIRST 2 YEARS														
DECK SHELL & FRAME					LIMITED LIFETIME DECK SHELL & FRAME														
ATTACHMENTS & ACCESSORIES																			
MULCHING KIT, ONE-WHEEL SULKY, TWO-WHEEL SULKY, OCDB KIT, LIGHT KIT, GRASS COLLECTOR, OCDB KIT																			

