



HD LOW PROFILE POWER TILT DECKOVER - BUMPER PULL

	8.5' x 22' (15K)	8.5' x 22' + 4' (15K)	8.5' x 22' (17.6K)	8.5' x 22' + 4' (17.6K)
Model #	ST10222DOT2A-B-150	ST102224DOT2A-B-150	ST10222DOT2A-B-176	ST102224DOT2A-B-176
GVWR (lb.)	15000		17600	
GAWR (lb. / axle)	7000		8000	
Curb Weight	4485	5170	4825	5370
Payload	10515	9830	12775	12230
Main Frame	W10 x 12#/ft., I-Beam			
Side Rails	6 x 2, 3/16 Wall Tube			
Cross Members	3" C-Channel (16" On-Center)			
Coupler	Adjustable Pintle Eye Coupler		Adjustable 4-Bolt Pintle Eye Coupler	
Jack	Setback HD 12K Drop Leg Jack			
Axles	E-Z Lube Electric Brake			
Suspension	Slipper Leaf Spring			
Tires	235/80R16 LRE		215/75R17.5 LRH	
Wheels	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	
Decking	2" Pressure Treated Pine			
Lights	All LED Lights			
Electric Plug	7-Way RV-Style Molded Plug			
Finish	Powder Coat High Gloss Black			
Overall Length	330"	378"	330"	378"
Deck Height	34"	34"	34"	34"
Coupler Height	Adjustable 21" - 29"			
Hydraulic Hoist	Dual Ram (Power Up / Power Down)			
Pump	3000 PSI Pump with Reservoir			
Battery	12-Volt Deep Cycle, DP24			
Load Angle	15 Degrees			

HD LOW PROFILE POWER TILT DECKOVER - BUMPER PULL FEATURES

HD I-Beam Tongue HD Tube Bulkhead Adjustable Pintle Eye Coupler (15K Models) Adjustable 4-Bolt Pintle Eye (17.6K Models) Safety Chains 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness Setback HD 12K Drop Leg Jack HD Slipper Spring Axles	Easy Lube Hubs 16" Radial Tires (15K Models) 17.5" Radial Tires (17.6K Models) Silver Wheels Wheel Assembly, 235 80R16 LRE (15K Models) Wheel Assembly, 215 75R17.5 (17.6K Models) Powder Coat Finish Pressure Treated 2" x 6" Decking Diamond Plate Deck Over Wheels (6) 5/8" D-rings	(8) 5/8" D-rings (+4 Models) Chain Spools Stake Pockets and Rub Rail Spare Tire Carrier Side Steps Tongue Mounted HD Control Box with Key Lock All LED Lights Deep Cycle Battery Battery Charger, 110-Volt Power-Up, Power-Down Hydraulics (Dual Ram)
--	---	--





HD LOW PROFILE POWER TILT DECKOVER - GOOSENECK

	8.5' x 22' (15K)	8.5' x 22' + 4' (15K)	8.5' x 22' (17.6K)	8.5' x 22' + 4' (17.6K)
Model #	ST10222DOT2A-GN-150	ST102224DOT2A-GN-150	ST10222DOT2A-GN-176	ST102224DOT2A-GN-176
GVWR (lb.)	15000		17600	
GAWR (lb. / axle)	7000		8000	
Curb Weight	4775	5460	5115	5660
Payload	10225	9540	12485	11940
Main Frame	W10 x 12#/ft., I-Beam			
Side Rails	6 x 2, 3/16 Wall Tube			
Cross Members	3" C-Channel (16" On-Center)			
Coupler	Adjustable 2-5/16" Gooseneck Coupler			
Jack	Dual Setback HD 12K Drop Leg Jacks with Toolbox			
Axles	E-Z Lube Electric Brake			
Suspension	Slipper Leaf Spring			
Tires	235/80R16 LRE		215/75R17.5 LRH	
Wheels	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	
Decking	2" Pressure Treated Pine			
Lights	All LED Lights			
Electric Plug	7-Way RV-Style Molded Plug			
Finish	Powder Coat High Gloss Black			
Overall Length	378"	426"	378"	426"
Deck Height	34"	34"	34"	34"
Coupler Height	Adjustable 31" - 39-3/4"			
Hydraulic Hoist	Dual Ram (Power Up / Power Down)			
Pump	3000 PSI Pump with Reservoir			
Battery	12-Volt Deep Cycle, DP24			
Load Angle	15 Degrees			

HD LOW PROFILE POWER TILT DECKOVER - GOOSENECK FEATURES

HD I-Beam Frame I-Beam Gooseneck HD Tube Bulkhead Adjustable 2-5/16" Gooseneck Coupler Safety Chains 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connections Dual Setback HD 12K Drop Leg Jacks with Toolbox	HD Slipper Spring Axles Easy Lube Hubs 16" Radial Tires (15K Models) 17.5" Radial Tires (17.6K Models) Silver Wheels Wheel Assembly, 235 80R16 LRE (15K Models) Wheel Assembly, 215 75R17.5 (17.6K Models) Powder Coat Finish Pressure Treated 2" x 6" Decking Diamond Plate Deck Over Wheels	(6) 5/8" D-rings (8) 5/8" D-rings (+4 Models) Chain Spools Stake Pockets and Rub Rail Spare Tire Carrier Side Steps All LED Lights Deep Cycle Battery Battery Charger, 110-Volt Power-Up, Power-Down Hydraulics (Dual Ram)
--	--	---

