



SPECIALTY NARROW SERIES

SPECIALTY
NARROW
SERIES

You move with purpose. Every task, every pass, and every day is an opportunity to drive your operation forward. As a specialty grower, your goals are ambitious: higher yields, better quality, and greater efficiency.

Kubota's specialty narrow tractors are built for that ambition. Compact, precise, and powerful, they're engineered to maneuver through narrow passages and deliver the horsepower you need to keep working all day. These tractors are designed to match your crops, your land, and your vision.

Because at Kubota, we design solutions that let you turn challenges into opportunities. Solutions that let you do what you do best – but on your own terms.

Because You Can.





COMPACT NARROW: THE PERFECT FIT

At 35.4"-53.7" wide, they're built to handle numerous applications in tight spaces with strength and reliability.



35.4"
B2401

39.4"
LX3520

53.7"
L4802

All-Day Comfort

For long hours in the field, Kubota's tractors provide a comfortable operator experience with an ergonomic platform, intuitive controls, and design features that help support a smooth operation.

Strength That Delivers

With rugged durability and a horsepower range to fit your needs, these compact tractors are ideal for mowing, hauling, and working through tight spaces without missing a beat. Gear-driven transmissions help to ensure dependable performance season after season.

	B2401 Narrow	LX3520 Narrow	L4802 Narrow
Diesel Engines			
Engine Gross Horsepower*	21.9	34.9	48.4
Power Take-Off (PTO) Horsepower	19.2	29.6	40.5
Gear Drive Transmissions			
Reverse Gears	3	12	8
Forward Gears	9	12	8

*SAE J1995 Gross Engine Power

B2401 Narrow

At just 35.4" wide, the B2401 Narrow is designed for the tight row spacings, fitting rows as close as 48" apart with ease. At only 1,334 lbs., its light build helps keep you agile from the first pass to the last. Compact yet capable, this lightweight tractor is purpose-built for vineyards, greenhouses, and nurseries where precision and care matter most.

■ Three-Point Hitch (24 in. behind)

Lift capacity of 1,301 lbs.

■ Rear Hydraulics

Two optional rear remotes to accommodate more implements.



LX3520 Narrow

At 39.4" wide, this compact powerhouse delivers four-cylinder turbo diesel performance in tight quarters, perfect for mowing and spraying between dense rows. The LX3520 Narrow can easily maneuver through orchards, vineyards, and nurseries.

■ Three-Point Hitch (24 in. behind)

Lift capacity of 1,819 lbs.

■ Dual Memory RPM switches

Save two frequently used engine speeds to instantly select without manually adjusting the throttle.

■ Foldable Center ROPS*

Perfect for compact environments, the foldable center ROPS allows for easy maneuverability in tight spaces, under low trees, around overhead obstructions, and effortless storage in limited spaces.

■ Hydraulic Independent PTO

The independent PTO allows the operator to stay productive by engaging and disengaging PTO while traveling forward and backward with ease.

■ Reliable Gear Drive Transmission

With synchronized main gear shift, the LX3520 Narrow offers dependable operation, catering to a wide range of jobs and applications suitable for this nimble tractor.

■ Mechanical Draft Control

Automatically adjusts the three-point hitch when utilizing ground engaging implements.

■ Optional Rear Hydraulics

LX3520 Narrow offers two optional rear remotes to accommodate additional rear implements.



*Roll Over Protective Structure (ROPS)

L4802 Narrow

Powered by a four-cylinder engine with 48.4 gross horsepower, the L4802 Narrow delivers added strength where space is limited. At 53.7" wide, it's specifically engineered to work in narrow spaces. This tractor delivers power and traction without sacrificing maneuverability, making it perfect for towing, mowing, and covering hilly ground. The L4802 Narrow comes standard with rubber floor mats, LED headlights and work lights. With a modern design and an open platform, you can stay comfortable when moving from row to row.

■ Three-Point Hitch (24 in. behind)

Lift capacity of 2,320 lbs.

■ Foldable Center ROPS

Conveniently fold down the ROPS for low trees, overhead obstructions or limited storage space and enhanced visibility.

■ Hydraulic Independent PTO

Boost efficiency with seamless PTO control. Engage or disengage the PTO on the move—forward or reverse—without ever stopping.

■ Standard Versatility

The L4802 Narrow comes standard with a set of rear remotes, making it ready for a variety of applications.







M NARROW

Built for growers who demand quality and dependability. The M Narrow tractors offer the power, hydraulic capacity, and maneuverability needed in vineyards and orchards ensuring the right fit for any specialty requirement.

Diesel Engines	M4N	M5N ROPS	M5N Cab
Rated Engine Horsepower*	72.6	92.6-105.7	95.0-108.2
Power Take-Off (PTO) Horsepower	61.0	75-91	75-91
Hydraulic Flow Rate (gpm)	16.7	16.7	18.1

* 97/68/EC



M4N

Full-size power in a narrow build. The M4N's 72.6 HP Kubota diesel engine handles large sprayers, harvest trailers, and flail mowers with ease. Designed with a streamlined frame for agile movement in narrow rows. Available with ROPS and cab options and 12-speed transmission, the climate-controlled cab offers wide visibility and quiet comfort for long days.

■ Versatile Transmission

Twelve-speed gearing provides optimal speed for every application.

■ Reliable Hydraulics

Sufficient flow for sprayers and specialty implements.

■ All-Season Capability

Built to handle bin trailers, flail mowers, and year-round tasks.

M5N + Power Krawler

Maximum power meets ultimate versatility. The M5N represents the pinnacle of narrow tractor capability, delivering multiple horsepower segments to meet the demands of specialized operations. Whether you're managing steep vineyard slopes, operating heavy-duty implements, or working extended hours, the M5N is built to adapt to your needs.

■ Transmission Flexibility

Choose between 12-speed for precision or 24-speed for maximum efficiency.

■ Power Krawler Option

Track system provides superior traction on steep, uneven terrain.

■ Professional Comfort

Spacious cab and platform built for comfort throughout the workday.

■ Heavy-Duty Hydraulics

High-flow systems power large sprayers and specialty implements.



COMPACT NARROW SPECIFICATIONS

B2401 Narrow

LX3520 Narrow

L4802 Narrow

ENGINE

Model		D1105-E4-D35	V1505-CR-TE5-D40R6	V2403-CR-E5-LB1
Indirect Injection, Vertical, Water-Cooled, 4-Cycle Diesel		●		
Direct Injection, Vertical, Water-Cooled, 4-Cycle Diesel			●	●
Turbocharger			●	
Cylinders		3	4	4
Bore and Stroke	<i>in (mm)</i>	3.07 × 3.09 (78 × 78.4)	3.10 × 3.10 (78 × 78.4)	3.43 × 4.03 (87 × 102.4)
Engine Gross Power*	<i>HP (kW)</i>	21.9 (16.3)	26.0 (34.9)	36.1 (48.4)
Engine Oil (with filter)	<i>qts (L)</i>	3.3 (3.1)	5.0 (4.7)	8.7 (8.2)
Engine Coolant	<i>qts (L)</i>	4.1 (3.9)	4.5 (4.3)	6.9 (6.5)
Fuel Tank	<i>gal (L)</i>	6.1 (23.0)	8.5 (32.0)	13.5 (51.0)
Maximum Net Torque	<i>lbf x ft (N x m)</i>	52.9 (71.7)	86.8 (117.5)	109.9 (149.0)
Rated Revolution	<i>RPM</i>	2600		
Total Displacement	<i>in³ (L)</i>	68.5 (1123)	91.4 (1498)	148.5 (2434)
Transmission Case	<i>gal (L)</i>	3.3 (12.5)	5.5 (21.0)	40.0 (10.6)

DIMENSIONS

Overall Length (without 3-point)	<i>in (mm)</i>	92.9 (2360)	98.2 (2494)	117.7 (2990)
Overall Width (minimum tread)	<i>in (mm)</i>	35.4 (900)	39.4 (1000)	53.7 (1365)
Overall Height – ROPS	<i>in (mm)</i>	75.2 (1910)	84.0 (2134)	94.9 (2410)
Overall Height (top of steering wheel)	<i>in (mm)</i>	51.26 (1302)	54.72 (1390)	59.8 (1520)
Wheelbase	<i>in (mm)</i>	61.4 (1560)	61.0 (1550)	72.6 (1845)
Minimum Ground Clearance	<i>in (mm)</i>	11.8 (300)	12.8 (325)	11.6 (295)
Tread – Front	<i>in (mm)</i>	27.8 (705)	33.1 (842)	41.5 (1055)
Tread – Rear	<i>in (mm)</i>	27.6, 31.1 (700, 790)	30.6 (778)	41.3 (1050)
Weight – ROPS	<i>lbs (kg)</i>	1334 (605)	2154 (977)	3362 (1525)

POWER TAKEOFF

PTO HP Power	<i>HP (kW)</i>	19.2 (14.3)	22.1 (29.6)	30.2 (40.5)
--------------	----------------	-------------	-------------	-------------

*SAE J1995 Gross Engine Power

M NARROW SPECIFICATIONS

	M4N-071HDC12* M4N-071HD12*		M5N-091HDC12 (HDC24)* M5N-092HD12 (HD24)*		M5N-091 Power Krawler	M5N-111HDC12 (HDC24)* M5N-112HD12 (HDC24)*		
	Cab	ROPS	Cab	ROPS	Cab	Cab	ROPS	
ENGINE								
Model	V3800-TE4 ¹		V3800-TIEF4 ²		V3800-TIEF4 ²	V3800-TIEF4 ²		
Cylinders	4		4		4	4		
Rated Engine Horsepower ³ <i>HP (kW)</i>	72.6 (54.1)		95 (70.8)	92.6 (69.1)	92.6 (69.1)	108.2 (80.7)	105.7 (78.8)	
Power Take-Off Horsepower at Rated RPM ⁴ <i>HP (kW)</i>	61 (45.5)		12-speed: 78 (58.1) 24-speed: 75 (55.9)		78 (N/A)	12-speed: 91 (67.9) 24-speed: 88 (65.6)		
Rated Speed <i>RPM</i>	2400		2600	2400	2600	2600	2400	
Total Displacement <i>in³ (L)</i>	230 (3769)		230 (3769)		230 (3769)	230 (3769)		
Fuel Tank <i>gal (L)</i>	20.1 (76)		20.1 (76)		20.1 (76)	20.1 (76)		
Alternator <i>amp</i>	Standard: 100 Option: 130	Standard: 100 Option: N/A	Standard: 80 Option: 130	Standard: 100 Option: N/A	Standard: 80 Option: 130	Standard: 80 Option: 130	Standard: 100 Option: N/A	
TRANSMISSION								
Number of Speeds (Standard or Optional)	12-speed: 12F/12R and 18F/18R with creep		12-speed: 12F/12R or 18F/18R with creep 24-speed: 24F/24R or 36F/36R with creep		12-speed: 12F/12R or 18F/18R with creep	12-speed: 12F/12R or 18F/18R with creep 24-speed: 24F/24R or 36F/36R with creep		
Main Gear Shift ⁵	6		6		6	6		
Range Gear Shift	Standard: 2 Option: 3 with creep		Standard: 2 Option: 3 with creep		Standard: 2 Option: 3 with creep	Standard: 2 Option: 3 with creep		
Electro-Hydraulic Shuttle	●		●		●	●		
Dual Speeds (Hi - Lo)	N/A		24-speed: Standard		24-speed: Standard	24-speed: Standard		
Max. Traveling Speed <i>mph (km/h)</i>	22.2 (35.2)		12-speed: 22.0 (35.2) 24-speed: 22.2 (35.6)		12-speed: 17.8 (28.5)	12-speed: 22.0 (35.2) 24-speed: 22.2 (35.6)		
Hydraulic Wet Disc Brake	●		●		●	●		
Four-Wheel Brake	●		●		●	●		
HYDRAULICS								
Open Center System	●		●		●	●		
Pump Capacity ⁶ <i>gpm (L/m)</i>	16.7 (63.3)		18.1 (68.6)	16.7 (63.3)	18.1 (68.6)	18.1 (68.6)	16.7 (63.3)	
Position and Draft Control System ⁷	●		●		●	●		
Telescopic Stabilizers ⁸	●		●		●	●		
Lift Capacity ⁸ <i>lbs (kg)</i>	3307 (1500)		3307 (1500)		3307 (1500)	3307 (1500)		
DIMENSIONS								
Overall Length <i>in (mm)</i>	149.2 (3790)	147.6 (3750)	155.5 (3950)	156.3 (3970)	155.5 (3950)	155.5 (3950)	156.3 (3970)	
Overall Width <i>in (mm)</i>	48.0 (1220)	51.6 (1310)	48.0 (1220)	51.6 (1310)	54.8 (1370)	48.0 (1220)	51.6 (1310)	
Overall Height <i>in (mm)</i>	90.2 (2290)	N/A	90.2 (2290)	N/A	93.3(2370)	90.2 (2290)	N/A	
Wheelbase <i>in (mm)</i>	83.9 (2130)		83.9 (2130)	83.6 (2123)	N/A	83.9 (2130)	83.6 (2123)	
Front Axle Crop Clearance <i>in (mm)</i>	14.6 (370)	12 (305)	14.6 (370)	12 (305)	14.6 (370)	14.6 (370)	12 (305)	
Turning Radius ⁹ <i>in (mm)</i>	12.5 (3.8)	12.1 (3.7)	12.5 (3.8)	12.8 (3.9)	12.9 (3.95)	12.5 (3.8)	12.8 (3.9)	
Front Tire	8.0-16		8.0-16		9.5-16	8.0-16		
Rear Tire	12.4-24		12.4-24		Tracks	12.4-24		
Weight <i>lbs (kg)</i>	5291 (2400)	5049 (2290)	5622 (2550)	5379 (2440)	7275 (3300)	5622 (2550)	5379 (2440)	
POWER TAKE-OFF								
Live-Independent PTO, Electro-Hydraulic Clutch with Brake	●		●		●	●		
Speed <i>RPM</i>	540/540E 540E		540/540E 540E		540/540E 540E	540/540E 540E		

*HDC12, HD12, HDC24, and HD24 (HD = hydraulic shuttle transmission, dual traction; C = cab; 12 = 12×12 transmission; 24 = 24×24 transmission)

¹4-cylinders in-line, common rail system, direct injection, DPF, DOC. ²4-cylinders in-line, common rail system, direct injection, DPF, DOC, SCR. ³97/68/EC. ⁴OECD CODE2.

⁵Speeds synchronized. ⁶3-point hitch. ⁷Top link sensing. ⁸24 inch behind lift point. ⁹Without brake and with bi-speed.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



For more information, go to [kubotausa.com/products/tractors/specialty](https://www.kubotausa.com/products/tractors/specialty).

