



## A CUT ABOVE OTHER CUTTERS

### **BOBCAT SOD CUTTERS**

Effortlessly cut more sod, more efficiently with Bobcat® sod cutters. With a 4.8 hp Honda® GX160 engine that reaches a 2 mph cutting speed and 4 mph transport speed, these machines are built to help you make quick work of any sod cutting job.

Four powerful models allow you to cut sod up to 2.5 inches thick at widths of 12, 18 or 24 inches. Easily take on the heaviest, most challenging soils with tread turf wheels that are designed to work on turf without damaging or tearing it. Enjoy the increased maneuverability of the hydrostatic drive, which allows for reverse operation, increasing your productivity during even the toughest tasks. It's no wonder Bobcat sod cutters are a cut above the rest.

# CUTTING-EDGE COMFORT AND CONTROL

Built to tackle the most challenging cutting jobs, Bobcat sod cutters are engineered for lasting toughness and durability. They offer user-friendly operation and effortless handling with minimal vibration for all-day comfort.



## Increased Durability

Equipped with a signature cast-iron gearbox, a sturdy front bumper and a laser-cut blade that sharpens itself as it wears down, Bobcat sod cutters are designed for superior cutting performance and longevity.

## Intuitive Operation

A conveniently mounted throttle lever on the operator station provides easy access during operation. A QR code is also located on the operator station for easy access to information about how to use your sod cutter effectively.

## Easy Handling

Enjoy smooth operation and reversing with the variable traction level of the hydrostatic drive. And you'll stay comfortable throughout the day with ultra-low vibration technology that reduces fatigue and enhances overall user experience.

## Enhanced Safety

The latch-locked blade lever prevents accidental activation of the blade until pressed, ensuring secure operation and increased user safety.

	SC12	SC18	SC18 <sub>H</sub>	SC24 <sub>H</sub>
<b>HONDA Engine</b>	<b>4-Cycle GX160</b>	<b>4-Cycle GX160</b>	<b>4-Cycle GX160</b>	<b>4-Cycle GX160</b>
Displacement	9.9 cu. in. (163 cc)	9.9 cu. in. (163 cc)	9.9 cu. in. (163 cc)	9.9 cu. in. (163 cc)
Fuel Capacity	0.8 gal. (3.1 L)	0.8 gal. (3.1 L)	0.8 gal. (3.1 L)	0.8 gal. (3.1 L)
Oil Capacity	0.6 qt. (0.5 L)	0.6 qt. (0.5 L)	0.6 qt. (0.5 L)	0.6 qt. (0.5 L)
<b>BRIGGS &amp; STRATTON® Engine</b>	<b>4-Cycle Vanguard™ 200 Model 12V3</b>	<b>4-Cycle Vanguard 200 Model 12V3</b>	–	–
Displacement	12.4 cu. in. (203 cc)	12.4 cu. in. (203 cc)	–	–
Fuel Capacity	0.8 gal. (3.1 L)	0.8 gal. (3.1 L)	–	–
Oil Capacity	0.6 qt. (0.6 L)	0.6 qt. (0.6 L)	–	–
Clutch	Spring-Loaded Belt Tightener	Spring-Loaded Belt Tightener	–	–
Max. Adjustable Cutting Thickness	2.5 in. (64 mm)	2.5 in. (64 mm)	2.5 in. (64 mm)	2.5 in. (64 mm)
Cutting Width	12.0 in. (305 mm)	18.0 in. (457 mm)	18.0 in. (457 mm)	24.0 in. (610 mm)
Max. Forward Speed	135 ft./min. (41 m/min.)	135 ft./min. (41 m/min.)	352 ft./min. (107 m/min.)	352 ft./min. (107 m/min.)
Max. Reverse Speed	–	–	176 ft./min. (54 m/min.)	176 ft./min. (54 m/min.)
Drive Wheel Diameter	8.0 in. (203 mm)	8.0 in. (203 mm)	8.0 in. (203 mm)	8.0 in. (203 mm)
Rear Tires	9 x 3.50-4	9 x 3.50-4	9 x 3.50-4	9 x 3.50-4
Weight: Wet	333 lb. (151 kg)	373 lb. (169 kg)	380 lb. (172 kg)	398 lb. (181 kg)
Width	25.0 in (635 mm)	25.0 in (635 mm)	25.0 in (635 mm)	25.0 in (635 mm)
Length	52.5 in. (1331 mm)	52.5 in. (1331 mm)	52.5 in. (1331 mm)	52.5 in. (1331 mm)
Height	39.5 in. (1003 mm)	39.5 in. (1003 mm)	40.2 in. (1022 mm)	40.2 in. (1022 mm)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

**DOOSAN**

**Bobcat Company is a member of the Doosan Group.** Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2023 Bobcat Company. All rights reserved.



**B-3062 (10/23)**  
EP-XXX-1023-7338-F

**Bobcat Company**  
250 East Beaton Drive • West Fargo, ND 58078  
**Bobcat.com**



**Bobcat®**

**One Tough Animal.**