

XHP750WCU-T4F

| Model | XHP750 |
|-----------------------------------------------|--------------------|
| COMPRESSOR | |
| Free-Air Delivery – cfm (m ³ /min) | 750 (21.2) |
| Rated Operating Pressure – psig (bar) | 350 (24.1) |
| Pressure Range – psig (bar) | 140-365 (9.7-24.1) |
| Air Discharge Outlet NPT Size – in (mm) | 2 (50.8) |
| Air Discharge Outlet Quantity | 1 |
| Compressor Oil Capacity – gal (L) | 26.7 (101) |
| ENGINE | |
| Engine Make/Model | Cummins/QLS9 |
| Emissions Tier Level | Tier 4 Final (T4F) |
| # of Cylinders | 6 |
| Displacement – cu in (L) | 543 (8.9) |
| Rated Speed – rpm | 1800 |
| Idle Speed – rpm | 1350 |
| Bhp @ Rated Speed (kW) | 340 (254) |
| Electrical – volts | 24 |
| Engine Oil Capacity – qt (L) | 23.2 (22) |
| Radiator Coolant Capacity – gal (L) | 15.3 (58) |
| Altitude Capability – ft (m) | 9000 (2743) |
| Fuel Consumption @ 100% load – gph (L/h) | 15.9 (60.2) |
| Fuel Tank Capacity – gal (L) | 128.1 (485) |
| DEF Tank Capacity - gal (L) | 10 (38) |
| DIMENSIONS WITH RUNNING GEAR | |
| Overall Length – in (mm) | 226.3 (5748) |
| Overall Width – in (mm) | 82.6 (2099) |
| Overall Height – in (mm) excluding exh pipe | 101.3 (2573) |
| Track Width – in (mm) | 69.3 (1760) |
| Tire Size – in | 16 |
| Shipping Weight w/o fuel – lb (kg) | 11067 (5020) |
| Working Weight w/ fuel – lb (kg) | 12213 (5540) |
| DIMENSIONS WITHOUT RUNNING GEAR | |
| Overall Length – in (mm) | 171 (4343) |
| Overall Width – in (mm) | 83 (2109) |
| Overall Height – in (mm) w/ shockmounts | 95 (2413) |
| Shipping Weight w/o fuel – lb (kg) | 10346 (4693) |
| Working Weight w/ fuel – lb (kg) | 11669 (5293) |

**MAKE POWER MOVES.****DoosanPowerMoves.com | 800.633.5206**

© 2020 Doosan Portable Power. All rights reserved.

Doosan reserves the right to limit quantities, alter lead times or cancel models without prior notice or obligation. Nothing contained in this brochure intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale shall be in accordance with standard Doosan Portable Power terms and conditions of sale for such products, which are available upon request. Specifications in this brochure are subject to change without notice.