



Bobcat

One Tough Animal

PA460v PORTABLE AIR COMPRESSOR

SPECIFICATIONS

	PA460v
COMPRESSOR ROTARY SCREW / SINGLE STAGE	
Free-Air Delivery (low/high)	460–350 cfm (13–9.9 m ³ /min)
Rated Operating Pressure (low/high)	100/175 psig (6.9–12.1 bar)
Pressure Range	80–175 psig
Air Discharge Outlet NPT Size	1.25 in (31.8 mm)
Air Discharge Outlet Quantity	1
Fuel Tank Capacity	60 gal (227 l)
ENGINE	
Make & Model	Bobcat 3.4
Emissions Tier Level	Tier 4 Final (T4F)
Number of Cylinders	4
Displacement	208 cu in (3.4 l), 135 HP
Rated Speed	2500 rpm
Idle Speed	1550 rpm
Bhp @ Rated Speed	2500 rpm
Electrical	12 V
Hours of Operation	9
DIMENSIONS WITH RUNNING GEAR	
Length	155 in (3918 mm)
Width	79 in (1988 mm)
Height	76 in (1921 mm)
Track Width	68 in (1728 mm)
Tire Size	15 in (381 mm)
Shipping Weight (without fuel)	3909 lb (1774 kg)
Working Weight (with fuel)	4311 lb (1956 kg)
DIMENSIONS WITHOUT RUNNING GEAR	
Length	112 in (2845 mm)
Width	64 in (1626 mm)
Height	71 in (1804 mm)
Shipping Weight (without fuel)	3401 lb (1543 kg)
Working Weight (with fuel)	3893 lb (1766 kg)

KEY FEATURES

The new Bobcat® PA460v portable air compressor delivers dual air pressure options that automatically adjusts air flow and pressure based on the actual workload.

- The PA460v provides a versatile airflow ranging from 350 to 460 cfm at pressures between 175 and 80 psi.
- Engineered with larger access doors, dual spin-on separator elements and extended service intervals, making routine service more convenient than ever.
- Featuring a 4.3" display with vibrant colors and easy to read graphics for a user-friendly operating experience.
- Powered by a Bobcat engine, the PA460v is designed for years of reliable performance and durability.



Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

The images shown are for illustration purposes only and may not be an exact representation of the product.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries.

www.bobcat.com

©2026 Doosan Bobcat North America. All rights reserved.

