



For Earth, For Life
Kubota

Specifications

| Model | | | BX1880 | BX2380 | BX2680 | BX23S |
|---|--|---------------------|--|-----------------------------------|--------------|------------------------------|
| Engine | | | Liquid-cooled, 3-cylinder diesel | | | |
| Type | | | | | | |
| Model | | | Kubota D722 | Kubota D902 | Kubota D1005 | Kubota D902 |
| Engine gross HP at 3200 rpm** | | HP (kW) | 16.6 (12.4) | 21.6 (16.1) | 24.8 (18.5) | 21.6 (16.1) |
| PTO horsepower at 3200 rpm | | HP (kW) | 13.7 (10.2) | 17.7 (13.2) | 19.5 (14.5) | 17.7 (13.2) |
| Displacement | | cu.in. (cc) | 43.9 (719) | 54.8 (898) | 61.1 (1001) | 54.8 (898) |
| Fuel tank capacity | | gal. (l) | 6.6 (25) | | | |
| Drive train | | | | | | |
| Transmission | | | HST, High-Low gear shift (2 forward / reverse) | | | |
| Drive method | | | 4WD | | | |
| Brakes | | | Wet disc | | | |
| PTO | | | Live independent PTO (with hydraulic clutch) | | | |
| Rear | | | STD (540rpm) | | | |
| Mid | | | STD (2500rpm) | | | |
| Hydraulics | | | | | | |
| Pump output | | gpm (l/min.) | 6.2 (23.5) | | | |
| 3-point hitch | | | SAE Category I | | | Optional |
| Lift capacity @ 24" behind pin | | lbs. (kg) | 680 (310) | | | |
| Steering | | | Hydrostatic Power Steering | | | |
| Tire size | | | | | | |
| Front | | Turf/Bar/Industrial | 16x7.5-8 / 16x7.5-8 / N.A. | 18x8.5-10 / 18x8.5-10 / 18x8.5-10 | | 18x8.5-10 / N.A. / 18x8.5-10 |
| Rear | | Turf/Bar/Industrial | 24x12-12 / 24x12-12 / N.A. | 26x12-12 / 26x12-12 / 26x12-12 | | 26x12-12 / N.A. / 26x12-12 |
| Traveling speeds at rated engine rpm (Turf) | | Forward mph (km/h) | 0-7.8 (0-12.5) | 0-8.4 (0-13.5) | | |
| | | Reverse mph (km/h) | 0-5.9 (0-9.5) | 0-6.5 (0-10.5) | | |
| Dimensions | | | | | | |
| Length with 3-point hitch | | in. (mm) | 95.5 (2425) | | | 99.0(2515) w/ Front guard |
| Width | | in. (mm) | 44.1 (1120) | 45.1 (1145) | | |
| Height with ROPS | | in. (mm) | 81.9 (2080) | 83.1 (2110) | | 86.2 (2190) |
| Wheelbase | | in. (mm) | 55.1 (1400) | | | |
| Ground clearance (front axle) | | in. (mm) | 7.6 (193) | 8.4 (213) | | |
| Tread | | Front in. (mm) | 36.6 (930) | | | |
| | | Rear in. (mm) | 32.2 (820) | | | |
| Turning radius (w/o brake) | | feet (m) | 7.5 (2.3) | | | |
| Tractor weight (w/ROPS) | | lbs. (kg) | 1336 (606) | 1443 (650) | 1521 (670) | 1570 (712) ** |

** SAE J1995 ** w/Front guard, w/control valve assy

All information presented is based on data available at the time of posting and Kubota Tractor Corporation reserves the right to change the stated specifications without notice. Actual models may vary. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown using visual effects and/or shown with options and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices and actual models may vary. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product were designed or manufactured.



KUBOTA TRACTOR CORPORATION
1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

©2017 Kubota Corporation



Cat.No.J2117-01-US Printed in Japan.D.REX."17-OCT.

BX

KUBOTA DIESEL TRACTOR
BX Series
BX1880 / BX2380 / BX2680 / BX23S
Reliability. Comfort. Versatility.





MEET THE BX SERIES

| | |
|--------|------------------------------|
| BX1880 | 16.6 ENGINE HP / 13.7 PTO HP |
| BX2380 | 21.6 ENGINE HP / 17.7 PTO HP |
| BX2680 | 24.8 ENGINE HP / 19.5 PTO HP |
| BX23S | 21.6 ENGINE HP / 17.7 PTO HP |

EVOLUTION OF THE BX SERIES

20 YEARS IN THE MAKING

In 2000, Kubota established the sub-compact diesel tractor market so that even first time operators can comfortably and efficiently perform a variety of gardening, landscaping, and general property maintenance tasks. This series not only maximizes its performance and versatility, but also includes operator comfort and styling improvements thus being the best BX Series Kubota has built to date.



BX00
2001
Kubota enters North America with the sub-compact tractor category.



BX50 / BX24
2006
Further modern innovations and styling with the release of the BX50 Series.



BX70 / BX25D
2013
Started offering drive over mower decks and moved the location of the brake pedal to the left side for more comfort. The BX70 also introduced the quick hitch.



BX80 / BX23S
2017-Today
Introduced the Swift-Tach loader, single piece hood redesign and offers a third function valve kit. The R14 tires were also introduced in 2021.



BX30 / BX23
2004
Kubota expands the offering of the sub-compact by introducing the BX30 Series and the first TLB model.



BX60 / BX25
2009
BX60 introduces a higher horsepower model within the BX Series.



BX70 / BX25D-1
2015
Improved comfort by adding the reclining seat and foldable arm rests.

2000

2020

RELIABILITY

With a Kubota manufactured 3-cylinder diesel engine, HST transmission, all metal hood, fenders and chassis, the BX Series is Kubota engineered from front to rear making this a very reliable sub-compact tractor.

COMFORT

For a sub-compact tractor, the BX Series comfort is unmatched. With a flat operating station, tilt steering, ergonomic placement of levers and a deluxe seat, the BX Series prevents operator fatigue when working long hours on gardening, landscaping and property maintenance.

VERSATILITY

Kubota’s versatile multi-purpose tractor offers four affordable models ranging from 16.6 to 24.8 HP to help you achieve your everyday tasks. This sub-compact tractor comes with an assortment of Performance Matched Land Pride implements such as a box blade, quick hitch, and pallet fork just to name a few. The BX Series line up also offers the BX23S, a dedicated TLB to help you with all your digging jobs.



TABLE OF CONTENTS

| | | | |
|-------------|---------|-------------|--------------------------|
| Reliability | Comfort | Versatility | Implements / Accessories |
| P. 9 | P. 13 | P. 19 | P. 27 |



RELIABILITY



RELIABILITY



KUBOTA DESIGNED, KUBOTA MANUFACTURED

Front to rear, the Kubota tractor is designed and built by Kubota for our Kubota customers. You won't find a "Kubota" re-branded tractor built by others, only Kubota quality through and through.



PERFORMANCE-MATCHED KUBOTA DIESEL ENGINE

All the BX Series tractors are powered by reliable diesel engines built by Kubota exclusively for the BX Series. The BX1880 and BX2380/BX23S come with 16.6 and 21.6 horsepower diesel engines, while the BX2680 packs a 24.8-horsepower diesel engine under the hood. All three engines are 3-cylinder workhorses that offer enough muscle to tackle even your toughest jobs.



EASY MAINTENANCE WITH ONE-PIECE METAL HOOD

Strong and durable, the BX Series' metal hood provides convenient access to the engine and protection ensuring that your BX tractor continues to look as good as it performs.



RELIABLE 2-RANGE HST TRANSMISSION

HST offers fast and smooth forward and reverse speed and direction changes via treadle foot pedals that leave your hands free for steering and implement control for maximum performance.



COMFORT



COMFORT



COMPACT SIZE

With an overall length similar to a standard garden tractor, BX-Series tractors are easy to drive and can work smoothly even in tight spaces. The BX-Series' compact size also means they're gentle on turf. But don't be fooled by their compact dimensions - these tractors are powerful and capable of handling a wide variety of chores and projects.

ROPS HEIGHT

The BX80-Series has a ROPS height of less than 7 feet (except BX23S) so you can drive the BX through most standard garage door openings without folding down the ROPS.

GROUND CLEARANCE

The BX Series provides plenty of ground clearance - 7.5 inches for the BX1880 and 8.4 inches for BX2380 / BX2680 / BX23S (without mid-mount mower) - to get you over rocks and other objects in your path.



SPACIOUS OPERATOR AREA

Operator comfort has been enhanced by a fully flat deck layout with the brake on the left side, providing more room for your feet. The new design also improves operability.

HIGH-BACK RECLINING DELUXE SEAT

A new deluxe seat helps keep the operator working comfortably and efficiently, even on the most demanding of tasks. The high-back reclining seat is fully adjustable and equipped with adjustable armrests. Soft cushioning supports the back and legs for optimum operator comfort.

(Excluding BX1880)

TILT STEERING WHEEL

Repositioned for greater comfort and steering control, the BX80 Series steering wheel also tilts to accommodate operators of all shapes and sizes. *(Excluding BX1880)*





COMFORT



EASY TO READ INSTRUMENT PANEL

The new BX Series' instrument panel offers easy to read indicators for all of the vital information you need to keep your tractor running smoothly, safely, and efficiently. A single glance at the redesigned instrument panel tells you everything you need to know about the major functions and condition of your BX Series tractor. The large tachometer in the center features a convenient orange indicator for the optimum rpm range for loader/backhoe operations.

CRUISE CONTROL

Cruise control automatically maintains a constant speed, letting you take your foot off the forward pedal. It's the easy way to mow large areas or travel long distances. *(Optional on BX1880)*

ADDITIONAL FEATURES:

- Hydraulic Power Steering
- Left Side Brake Pedal
- Flat Floor for Increased Legroom
- Cup Holder
- Hand Rail
- 12V Socket & Storage Compartment
- Deluxe Lever Guide
- Foldable ROPS
- Tool Box *(Optional)*



OPTIONAL CAB AVAILABLE - 4070A AND 4090A

The best way to stay warm during your winter season applications is through the optional dealer installed BX cab. These new "A" version cabs are packed with the most popular optional features.

The new standard features for the new "A" version cabs include:

- Cab Heater
- Front LED Work Lights
- Front Windshield Wipers



VERSATILITY



PERFORMANCE MATCHED FRONT LOADERS - LA344 & LA340

Kubota’s front loaders are built by Kubota and specifically designed to maximize the performance of the front loader and tractor. The Kubota-built LA344 is designed for the BX1880, BX2380, and the BX2680 while the LA340 is designed for the BX23S. They offer a large lifting capacity, perfect for landscaping or light utility work. The curved boom matches the hood design for a sleek and modern appearance and offers a better field of vision during front loader operations.

UNIQUE SWIFT-TACH DESIGN

Attaching and detaching Kubota’s Swift-Tach front loader can be done in 4 easy steps all from the comfort of your seat. Simply follow the four steps listed below.



Step 1: Lift the loader boom and fully dump the bucket. Pull stand release lever to lower the front loader stand. Reposition the bucket so that it is in slightly dumped (20 degrees dump position) and lower the boom until the front axle is off the ground.



Step 2: Unlatch the loader latch levers to detach the front loader hooks.



Step 3: Use the loader lever to remove the loader frame from the mast. Turn off the engine and move the loader joystick lever to relieve the hydraulic pressure.



Step 4: Pull one lever to quickly and easily detach the hydraulic lines as a unit and store the coupler on the loader boom.

LOADER FEATURES



2-LEVER QUICK COUPLER

Kubota’s 2-lever quick couple speeds-up and simplifies the changing of front attachments.

HOSE PROTECTION

The loader hoses are tucked inside the boom for greater protection and better operator visibility. (LA344S)

3RD FUNCTION HYDRAULIC VALVE

The optional 3rd function hydraulic valves are used for front attachments that require hydraulic power such as grapples.

| Front Loader Specifications | | | | | | | |
|---|-----------|--------------|---------------|---------------------|---------------|--------------|---------------------|
| Model Type | | LA344 Pin-On | | LA344S Quick Attach | | LA340 Pin-On | LA340S Quick Attach |
| | | BX1880 | BX2380/BX2680 | BX1880 | BX2380/BX2680 | BX23S | |
| Max Lift Height (to bucket pivot pin) | in. (mm) | 70.7 (1795) | 71.0 (1804) | 70.7 (1795) | 71.0 (1804) | 71.0 (1804) | |
| Dumping Clearance | in. (mm) | 51.8 (1316) | 52.1 (1323) | 50.4 (1281) | 50.7 (1288) | 52.1 (1323) | 50.7 (1288) |
| Dumping Reach at Max. Lift Height | in. (mm) | 25.3 (642) | 25.4 (646) | 26.5 (673) | 26.7 (677) | 25.4 (646) | 26.7 (677) |
| Maximum Dump Angle | degrees | 45 | | | | | |
| Reach with Bucket on Ground | in. (mm) | 55.0 (1398) | 54.8 (1392) | 56.9 (1445) | 56.6 (1438) | 54.8 (1392) | 56.6 (1438) |
| Bucket Rollback Angle | degrees | 30 | 29 | 30 | 29 | 29 | |
| Digging Depth | in. (mm) | 5.3 (134) | 4.9 (125) | 5.2 (132) | 4.8 (122) | 4.9 (125) | 4.8 (122) |
| Bucket Width | in. (mm) | 48 (1219) | | | | | |
| Lift Capacity (500mm fwd, max, height) | lbs. (kg) | 509 (231) | | 423 (192) | | 509 (231) | 423 (192) |
| Lift Capacity (pivot pin, max, height) | lbs. (kg) | 739 (335) | | 613 (278) | | 739 (335) | 613 (278) |
| Loader with Standard Bucket Weight | lbs. (kg) | 507 (230) | | 610 (277) | | 507 (230) | 610 (277) |
| Breakout Force (500mm fwd) | lbf. (N) | 978 (4389) | | 901 (4008) | | 987 (4389) | 901 (4008) |
| Raising Time / Lowering Time (w/o load) | second | 3.3 / 2.5 | | | | | |
| Bucket Rollback Time / Dumping Time | second | 2.3 / 2.7 | | | | | |



VERSATILITY



BX23S

From the moment you bring it home, the BX23S is ready to go to work loading, mowing, digging, and more. It comes with a performance-matched and fully integrated backhoe and front loader as standard equipment. Kubota's new Swift-Connect and Swift-Tach systems let you quickly and easily attach the backhoe (Swift-Connect) and front loader (Swift-Tach). A heavy-duty reinforced frame provides the durability, stability, and strength to complete any tough task.

KUBOTA SWIFT-CONNECT

A simple lever operation is all it takes to quickly detach the backhoe from the BX23S, letting you drive away. To reattach, just back the BX23S into the backhoe and let the auto-lock mechanism secure them together.

REVERSIBLE SEAT

When it's time to switch from using the tractor or loader to using the backhoe, simply lift the reversible seat and rotate it to the back. The seat can also be adjusted forward and backward for optimal operator comfort.

BOOM & SWING CYLINDER CUSHION VALVES

Standard on the BX23S, an integrated cushion valve ensures smooth movement both horizontally and vertically, minimizing the shock that's transmitted to the operator when the backhoe arm hits its range limits.

NO-SPILL COUPLER

The backhoe uses the same No-Spill coupler system as the front loader to help keep your backhoe clean and oil-free.

WIDE VIEW

The benefit of tucking the hydraulic hoses inside the backhoe boom provides greater protection for the hoses and greater visibility for the operator.



MECHANICAL THUMB *(Optional)*

A positionable mechanical thumb gives the BX23S the ability to grasp and move logs, landscaping materials, and other items with ease, greatly expanding the types of jobs you can do around your property.



| BX23S** Backhoe Specifications | | |
|---|-----------|--------------|
| Model | | BT603 |
| Bucket Cylinder Digging Force | lbf. (N) | 1936 (8610) |
| Dipperstick Cylinder Digging Force | lbf. (N) | 1171 (5209) |
| Boom Swing Mechanism | | One Cylinder |
| Backhoe Weight (with 12" bucket) | lbs. (kg) | 607 (275) |
| Transport Height | in. (mm) | 6.7 (1719) |
| Loading Height | ft. (mm) | 5' (1533) |
| Digging Depth | ft. (mm) | 6'1" (1842) |
| Swing Pivot to Rear Axle Center Line | in. (mm) | 28.6 (726) |
| Reach from Swing Pivot | ft. (mm) | 8'7" (2612) |
| Bucket Rotation | degrees | 180 |
| Swing Arc | degrees | 140 |
| Angle of Departure | degrees | 20.1 |
| *SAE J1995 **The loader and backhoe come standard on the BX23S model. | | |



MID-MOUNT MOWER

The versatile BX Series tractors are easy to drive and maneuver, letting you take on the most challenging mowing jobs with confidence and efficiency. BX Series tractors maneuver easily between trees and other tight places in the yard. Their compact size also means they're gentle on turf. The Easy-Over mid-mount mower deck is quick to attach and detach, and is available in two sizes—54" and 60"—to match your specific mowing needs.



STANDARD DECK

This 3-blade mower offers a wide cutting area, allowing you to cut more grass in a single pass. Choose a 48" /54" deck for the BX1880 or a 54" / 60" deck for the BX2380 / BX2680 / BX23S.



HIGH CLEARANCE

With 6 inches of clearance, the BX Series tractors easily travel over uneven ground and protruding obstacles.



MOWING-HEIGHT ADJUSTMENT DIAL

A simple twist of the dial adjusts the mower height in 1/4" increments to your desired cutting level.



EASY ATTACH/DETACH

The mower can be attached and detached quickly and easily— saving you time and effort.



DURABLE SHAFT DRIVE

The BX Series' shaft drive delivers power smoothly from the mid-PTO to the mid-mount mower. Unlike belt drives, there is no slippage and maintenance is minimal.

| Mid-Mount Mower Specifications | | | | |
|--|-----------|----------------------|-------------------------------------|---------------------------|
| Model | | RCK48-18BX | RCK54-23BX | RCK60B-23BX |
| | | BX1880 | BX1880 BX2380 BX2680 BX23S | BX2380 BX2680 BX23S |
| Type | | Side Discharge | | |
| Number of Blades | | 3 | | |
| Mounting Method | | Suspended-Linkage | | Self Balance |
| Cutting Width | in. (mm) | 48 (1219) | 54 (1372) | 60 (1524) |
| Cutting Height | in. (mm) | 1.0 - 4.0 (25 - 102) | | |
| Adjustment of Cutting Height | | 1/4" Dial Gauge | | |
| Weight | lbs. (kg) | 165 (75) | 201 (95) | 250 (115) |
| Ground Clearance in Transport Position | in. (mm) | 6.0 (152) | | |

| Easy-Over Mower Specifications | | | |
|--------------------------------|-----------|------------------|-----------|
| RCK54D-26BX-1 | | RCK60D-26BX-1 | |
| BX2380 BX2680 | BX23S | BX2380 BX2680 | BX23S |
| Side Discharge | | | |
| 3 | | | |
| Drive Over Suspended-Linkage | | | |
| 54 (1372) | | 60 (1524) | |
| 1.0 - 4.0 (25 - 102) | | | |
| 1/4" Dial Gauge | | | |
| 269 (122) | 258 (117) | 295 (134) | 284 (129) |
| 6.0 (152) | | | |



VERSATILE 4-POINT HITCH



The Kubota 4-point front hitch enables front implements like blades, brooms and snow blowers to be easily attached and removed.

- Available Implements:
- 48" Commercial / Heavy Duty Snow Blower
 - 50" Standard / Heavy Duty Snow Blower
 - 55" Standard / Heavy Duty Snow Blower
 - 60" Heavy Duty Sweeper
 - 60" Heavy Duty Blade



BUILT TO SUCCEED

From digging and scraping to mowing and plowing, there’s a BX Series implement that can do it faster, easier, and more efficiently. Kubota’s new hitch system lets you quickly and easily connect a much wider range of implements, including a Kubota pallet fork and snow blade, as well as implements from other manufacturers. Also available is the Land Pride 3-point quick hitch which will allow for easy attaching and detaching of approved 3-point implements, often without ever having to get off the tractor!



MID-MOUNT MOWER



PALLET FORK



GRADING SCRAPER



DISC HARROW



TRIP BLADE



GROOMING MOWER



GRAPPLE



POST HOLE DIGGER



REAR BLADE



SNOW BLOWER



ROTARY CUTTER



ROTARY TILLER



4-IN-1 BUCKET



BOX SCRAPER



SNOW BLADE

TIRES



R1 BAR/AGRICULTURAL
(BX1880, BX2380, BX2680 only)



R3 TURF
(All models)



R4 INDUSTRIAL
(BX2380, BX2680, BX23S only)



R14 HYBRID
(BX2380, BX2680, BX23S only)

TIRES OPTIONS

Kubota’s BX Series offers a variety of tire tread types. Turf tires are designed for minimal ground disruption, and industrial tires are designed for a more every day use style tread. The Goodyear’s new R14T hybrid is now available on the BX Series. This hybrid utilizes ag, turf, and industrial tread technology to provide powerful traction with minimal ground pressure.

AVAILABLE BX ACCESSORIES



WEIGHT BOX



QUICK HITCH



THIRD FUNCTION VALVE



CANOPY



WORK LIGHTS



CAB *(Snow Broom Shown)*